

Technical Data Sheet

BOondloc BGETGRP - Get a Grip

Revised 03.08.10



Bondloc Get A Grip

DESCRIPTION

Bondloc Get a Grip is a high viscosity multi-purpose panel adhesive. The high viscosity of this product allows non sagging bonding for light elements.

APPLICATIONS

Bondloc Get a Grip can be used for bonding wooden or rigid PVC skirtings and profiles, polyurethane and polystyrene beams, cornices and slabs, insulating and sound proofing materials.

USEFUL NOTES

- Gap filling up to 12mm
- Can be sanded
- Fast fixing of uPVC frames
- Can be painted
- Forms high strength bonds between most construction materials.

INSTRUCTIONS FOR USE

- Ensure surfaces to be bonded are even, dry and free from dust grease and any other contaminants.
- Cut off tip of cartridge and pierce internal membrane, screw nozzle on to cartridge and cut at a 45° angle to required width. Fit onto a cartridge gun.
- **Wet Bonding**
- Apply a zigzag bead along the item to be fixed, press firmly into place applying even pressure all over. Unsupported vertical items may require temporary support.
- Allow 24 hours before removing the support.
- On rough and uneven surfaces where gap filling is required apply sufficient adhesive to slightly over fill the gap.
- **Contact Bonding**
- Heavier items apply a bead as above, press in to place and then pull apart. Allow the adhesive to dry for 5 minutes, press firmly into place with even pressure all over.

TECHNICAL FEATURES

Colour	Light beige
Density at 20°C	1.50
Gap bridging	Up to 12mm
Application temperature	5 - 35°C
Tack free time	Instant
Cure system	Solvent evaporation
Sandability	Good
Paintability	Good
Temperature range	-10 - 70°C

STORAGE

Store in unopened cartridges.

HEALTH & SAFETY

This technical information sheet does not constitute a Material Safety Data Sheet (MSDS). Before using this product please ensure you have read and fully understood Bondloc Get a Grip MSDS.

PRESENTATION

Cartridge.....310ml

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.