

Technical Data Sheet

Bondloc BPVC – PVC Pipe Cement

Revised 03.08.10



BPVC – PVC Pipe Cement

PRODUCT DESCRIPTION

BPVC Pipe Cement is a non-drip, thixotropic solvent based pipe cement, it combines a long open time with a rapid rate of bond strength development.

APPLICATION

Ideal for bonding and repairing soft PVC/Vinyl plastics, inflatable beds, paddling pools, pond liners, tents, artificial leather and seat covers. Not suitable for pressure pipe applications.

INSTRUCTIONS FOR USE

- Stir well before use, the adhesive should flow slowly off the stick.
- In an axial direction apply the adhesive firstly to the inside of the socket and secondly to the pipe.
- Immediately insert the pipe into the socket to full depth without twisting or jamming.
- Hold for several seconds to allow the adhesive to begin to dry and remove any excess.
- The adhesive cures rapidly so the components must be completely joined within a minute.
- Do not dip pipe into adhesive.

TECHNICAL FEATURES

Appearance	Clear liquid
Specific gravity	0.97g/ml
Viscosity (Brookfield) SP4 23°C 30rpm	8000-15000 mPas

STORAGE

Store at temperatures above 5°C, temperatures below will lead to higher viscosity and thickening of the adhesive. Stored at 20°C Bondloc pipe cement will have a shelf life of 24 months.

HEALTH & SAFETY

This technical information sheet does not constitute a Material Safety Datasheet (MSDS). Before using this product ensure you have read and fully understood Bondloc Pipe Cement MSDS.

PRESENTATION

Tin.....500ml

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.