



1SN / 2SC JET WASH (BLUE)

Global Flex Hydraulic Hose

Recommended for all high pressure hydraulic & water based applications where a hardwearing, flexible hose is required



GLOBAL FLEX

SPECIFICATIONS

HOSE			INSIDE Ø		OUTSIDE Ø		WORKING PRESSURE		BURST PRESSURE	BEND RADIUS	WEIGHT
part number	dash size	DN	inch	mm	mm	bar	psi	bar	mm	kg/m	
GFJWB1SN06	-6	10	3/8	9.5	17.4	280	4000	840	90	0.34	
GFJWB1SN08	-8	12	1/2	12.7	22.2	280	4000	840	120	0.43	
GFJWB2SC04	-4	06	1/4	6.3	14.2	400	5800	1200	75	0.28	
GFJWB2SC06	-6	10	3/8	9.5	18.3	400	5800	1200	90	0.41	
GFJWB2SC08	-8	12	1/2	12.7	21.5	360	5200	1100	130	0.59	

Tube

Oil resistant synthetic rubber

Reinforcement

One or two high tensile steel wire braids

Cover

Oil and weather resistant synthetic rubber

Temperature

-40°C to +155°C

Additional Information

Also known as R&G SUPERJET



Global Flex Swaging Machines

Looking to make your own hydraulic hoses? Did you know Hydraulic Megastore offers a wide range of Global Flex swaging machines available in hand pump, air pump, 12V, single and three-phase.

We also offer 12V cutting machines for vehicle hose replacement and single phase and three-phase cutting machines for workshop locations. Contact our sales team today for more information!

30+ Years in the Hydraulic Industry

 **01472 255 928**

 www.hydraulicmegastore.com |  hello@hydraulicmegastore.com

 Unit 3 Estate Road 5, South Humberside Industrial Estate, Grimsby, North East Lincs, DN31 2TG

A PROUD PART OF

R&G
FLUID POWER GROUP



1SN / 2SC JET WASH (BLACK)

Global Flex Hydraulic Hose

Recommended for all high pressure hydraulic & water based applications where a hardwearing, flexible hose is required



GLOBAL FLEX

SPECIFICATIONS

HOSE		INSIDE Ø			OUTSIDE Ø		WORKING PRESSURE		BURST PRESSURE	BEND RADIUS	WEIGHT
part number	dash size	DN	inch	mm	mm	bar	psi	bar	mm	kg/m	
GFJWBLK1SC04	-4	06	1/4	6.3	13.4	280	4000	840	70	0.21	
GFJWBLK1SC06	-6	12	3/8	12.7	22.2	280	4000	840	120	0.43	
GFJWBLK2SC04	-4	06	1/4	6.3	14.2	400	5800	1200	75	0.28	
GFJWBLK2SC06	-6	10	3/8	9.5	18.3	400	5800	1200	90	0.41	

Tube

Oil resistant synthetic rubber

Reinforcement

One or two high tensile steel wire braids

Cover

Oil and weather resistant synthetic rubber

Temperature

-40°C to +155°C

Additional Information

Also known as R&G SUPERJET



Global Flex Swaging Machines

Looking to make your own hydraulic hoses? Did you know Hydraulic Megastore offers a wide range of Global Flex swaging machines available in hand pump, air pump, 12V, single and three-phase.

We also offer 12V cutting machines for vehicle hose replacement and single phase and three-phase cutting machines for workshop locations. Contact our sales team today for more information!

30+ Years in the Hydraulic Industry

 **01472 255 928**

 www.hydraulicmegastore.com |  hello@hydraulicmegastore.com

 Unit 3 Estate Road 5, South Humberside Industrial Estate, Grimsby, North East Lincs, DN31 2TG

A PROUD PART OF

R&G
FLUID POWER GROUP